## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

- 1. A fuel cartridge for a fuel cell, that is stored with liquid fuel to be directly supplied to a fuel electrode of the fuel cell and that is attachable and detachable to/from said fuel cell, is characterized in that the fuel cartridge comprises:
- a fuel supply part for supplying said liquid fuel to said fuel cell; and
  a fuel introduction part that can be opened and closed and that is used for refilling
  said liquid fuel into said fuel cartridge for said fuel cell.
- The fuel cartridge for the fuel cell according to Claim 1, is characterized in that
   an opening is arranged in a wall portion of a storage chamber stored with said
  liquid fuel,

said fuel introduction part includes said opening and a closing member for closing said opening, and

said closing member is attachable and detachable to/from said wall portion.

3. The fuel cartridge for the fuel cell according to Claim 1 or 2, is characterized in that said fuel supply part is arranged in said fuel introduction part.

## PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/000676

- 4. (Currently Amended) The fuel cartridge for the fuel cell according to Claim 1 or 2 to any one of Claims 1 to 3, is characterized in that said fuel supply part is sealed by a self-sealing member.
- 5. (Currently Amended) The fuel cartridge for the fuel cell according to <u>Claim 1 or 2 any</u> one of <u>Claims 1 to 4</u>, is characterized in that

the fuel cartridge comprises a first chamber for holding said liquid fuel; a second chamber to which effluent that has passed through said fuel electrode is introduced, and a partition wall for partitioning said first chamber and said second chamber,

said first chamber has said fuel supply part and said fuel introduction part, and said second chamber has an effluent recovery port to which said effluent recovered from said fuel electrode is introduced.

- 6. The fuel cartridge for the fuel cell according to Claim 5, is characterized in that said second chamber has an effluent discharge part that can be opened and closed and that is used to discharge said effluent.
- 7. The fuel cartridge for the fuel cell according to Claim 6, is characterized in that said effluent discharge part is provided with said effluent recovery port.

## PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/000676

- 8. (Currently Amended) The fuel cartridge for the fuel cell according to Claim 1 or 2 any one of Claims 5 to 7, is characterized in that said effluent recovery port is sealed by a self-sealing member.
- 9. (Currently Amended) The fuel cartridge for the fuel cell according to <u>Claim 1 or 2 any</u> one of <u>Claims 3 to 8</u>, is characterized in that a part of said fuel introduction part is made by a fuel absorption member that absorbs said liquid fuel, and wherein said fuel absorption member is arranged in said fuel cartridge.
- 10. The fuel cartridge for the fuel cell according to Claim 9, is characterized in that said fuel absorption member is attachable and detachable to/from said fuel introduction part
- 11. (Currently Amended) The fuel cartridge for the fuel cell according to <u>Claim 1 or 2</u> any one of <u>Claims 1 to 10</u>, is characterized in that said fuel cartridge can be stored in an electronic device.
- 12. (Currently Amended)-A fuel cell is characterized in that the fuel cell comprises a fuel cell main body having a fuel electrode; and the fuel cartridge for the fuel cell according to <u>Claim</u>

  1 or 2 any one of <u>Claims 1 to 11</u>, which is stored with liquid fuel to be directly supplied to said fuel electrode.